



TRANSPARENT LED DISPLAY

HIGH TRANSPARENCY DISPLAYS



Specifications

Model	P3.91	P7.81	P10.41	P3.91
Pixel pitch	3.91mm	7.81mm	10.41mm	3.91mm
Scan Mode	1/16	1/8	1/6	1/8
Pixel Density	32768dots/m ²	16384dots/m ²	9216dots/m ²	32768dots/m ²
Pixel Configuratio	1921	1921	1921	1921
Module Resolution	128X32	64X32	48X24	128X32
Module Size	500X250	500X250	500X250	500X250
Cabinet Size	500X500	500X500	500X500	500X500
Cabinet Resolution	128X64	64X64	48X48	128X64
Brightness(full white)	2500CD/m ²	2000CD/m ²	2500CD/m ²	5000CD/m ²
Refresh Rate	>1920HZ			
Packing Way	Wooden Cases Flight Cases	Wooden Cases Flight Cases	Wooden Cases Flight Cases	Wooden Cases Flight Cases
Transparency Rate	68%	68%	70%	68%
Weight(kg/m ²)	3.6kg	3.5kg	3.5kg	3.6kg
Viewing Angl	68%	68%	70%	68%
Power Consumptio (Max./Avg.)(W/m ²)	480/184W/m ²	480/184W/m ²	380/114W/m ²	900/340/m ²
Signal Input	HUB-BLP-V02	HUB-BLP-V02	HUB-BLP-V02	HUB-BLP-V02