AVOLUTION™

DIGITAL: POWERED BY HUMANS

MULTI-TOUCH

AVOlution Interactive Kiosk









Ultra Slim: 3.75 - 8 cm thickness. Stylish classic appearance with aluminum frame enclosure and built-in tempered glass. Perfectly intergrated into all kinds of applications.

HD stable Display: High quality ultra clear LCD Screen high brightness and superior color rendering.

Multiple Installation: Suitable for horizontal or vertical wall-mounted and floor standing installation.

Diverse customization: Single version/ network version (LAN / WIFI / 3G) / touch version, camera/ IR/ sensing/ Bluetooth / interactive touch screen and other expansion capabilities, all can be customized according to customer's specific requirements;







MANILA OFFICE:
231 B. Padilla St., Brgy. Santa Lucia, San Juan City, Philippines 1500
Tell.: (02) 8 631-2404

DAVAO OFFICE:
A. Bldg. 333 Gen. Douglas MacArthur Highway, Talomo District Brgy. Matina Crossing,Davao City
(082) 298 9004

AVOlutionInc
www.avolutioninc.net

AVOLUTION™

DIGITAL: POWERED BY HUMANS

43 INCH INTERACTIVE TOUCH SCREEN



MULTI-TOUCH

AVOlution Interactive Kiosk

SPECIFICATIONS

Model Size	**43 Inch**
Decoders	FULL HD Decoding Board
System	Windows
CPU (Optional)	i5 10th Gen/ 8 GB DDR4
Touch Function	IR Touch/ Capacitive Touch-
Touch Point	4 Point IR Touch/ 10 Point Capacitive Touch
Max Resolution Ratio	1920 X 1080 FHD / 3840 X 2160 4K
Viewing angle	178° (H);178° 0/) (Ratio 10)
Color	16.7M Color
Brightness	350 cd/m2
Contrast Ratio	1400:1
Response Time	Srns
Visable Area	930.66mm(H) x 523.04mm(V)
Storage Capacity	120G SSD
Dimensions	1795mm*650mm*68.30mm
Installation	Horizontal/ Vertical Wall-Mounted
Machine Net Weight	45kg
Support Video Encoding Fromat	MPEG-1, MPEG-2, AVI (3.11), XVID, H264
Support Image Format	BM JPEG, PNG, GIF
Support Audio Encoding Format	MPEG-1 Layer I II 11120, MPEG-4 AAC LCS.1 / HE AACS.1 / BSAC2.0, WAV 24-bit Linear PCM7.1
Volume	Adjusted by remote control
Auto Power On & Off	Support
Play Mode	Loop, insertion, timing, scheduled times play mode
Memory Mode Protection	Design with safety lock
RJ-45' Interface	10m / 100m x 1
USB2.0	**x4**
Infrared Input	Support
Power Supply Spec.	Voltage Range: 1OOVac to 240Vac
Speaker Power	10W
Max Consumption	320W
Stand-by Consumption	2W
Operating Temperature	0°c - 40°c
Operating Humidity	10% - 90%, no condensation
Storage Temperature	-20°C- 60°C

MANILA OFFICE:
231 B. Padilla St., Brgy. Santa Lucia, San Juan City, Philippines 1500
Tell.: (02) 8 631-2404

DAVAO OFFICE:
A. Bldg. 333 Gen. Douglas MacArthur Highway, Talomo District Brgy. Matina Crossing,Davao City
(082) 298 9004

AVOlutionInc
www.avolutioninc.net

AVOLUTION™

DIGITAL: POWERED BY HUMANS

49 INCH INTERACTIVE TOUCH SCREEN



iMULTI-TOUCH

AVOlution Interactive Kiosk

SPECIFICATIONS

Model Size	**49 Inch**
Decoders	FULL HD Decoding Board
System	Windows
CPU (Optional)	i5 10th Gen/ 8 GB DDR4
Touch Function	IR Touch/ Capacitive Touch-
Touch Point	4 Point IR Touch/ 10 Point Capacitive Touch
Max Resolution Ratio	1920 X 1080 FHD / 3840 X 2160 4K
Viewing angle	178° (H);178° 0/) (Ratio 10)
Color	16.7M Color
Brightness	350 cd/m2
Contrast Ratio	1400:1
Response Time	Sms
Visable Area	1073.66mm(H) x 604.04rnm(V)
Storage Capacity	120G SSD
Dimensions	1800mm*720mm*68.5mm
Installation	Horizontal/ Vertical Wall-Mounted
Machine Net Weight	45kg
Support Video Encoding Fromat	MPEG-1, MPEG-2, AVI (3.11), XVID, H264
Support Image Format	BM JPEG, PNG, GIF
Support Audio Encoding Format	MPEG-1 Layer I II 1112.0, MPEG-4 AAC LCS.1 / HE AACS.1 / BSAC2.0, WAV 24-bit Linear PCM7.1
Volume	Adjusted by remote control
Auto Power On & Off	Support
Play Mode	loop, insertion, timing, scheduled times play mode
Memory Mode Protection	Design with safety lock
RJ-45' Interface	10m / 100m x 1
USB2.0	**x4**
Infrared Input	Support
Power Supply Spec.	Voltage Range: 1OOVac to 240Vac
Speaker Power	10W
Max Consumption	320W
Stand-by Consumption	2W
Operating Temperature	0°c - 40°c
Operating Humidity	10% - 90%, no condensation
Storage Temperature	-20°C- 60°C

MANILA OFFICE:
231 B. Padilla St., Brgy. Santa Lucia, San Juan City, Philippines 1500
Tell.: (02) 8 631-2404

DAVAO OFFICE:
A. Bldg. 333 Gen. Douglas MacArthur Highway, Talomo District Brgy. Matina Crossing,Davao City
(082) 298 9004

AVOlutionInc
www.avolutioninc.net

AVOLUTION™

DIGITAL: POWERED BY HUMANS

55 INCH INTERACTIVE TOUCH SCREEN



MULTI-TOUCH

AVOlution Interactive Kiosk

SPECIFICATIONS

Model Size	**55 Inch**
Decoders	FULL HD Decoding Board
System	Windows
CPU (Optional)	i5 10th Gen/ 8 GB DDR4
Touch Function	IR Touch/ Capacitive Touch-
Touch Point	4 Point IR Touch/ 10 Point Capacitive Touch
Max Resolution Ratio	1920 X 1080 FHD / 3840 X 2160 4K
Viewing angle	178° (H); 178° 0/) (Ratio 10)
Color	16.7M Color
Brightness	350 cd/tn2
Contrast Ratio	1400:1
Response Time	Sms
Visable Area	1209.6mm(H) x 680.4mmM
Storage Capacity	120G SSD
Dimensions	1947mm*804mm*68.30mm
Installation	Horizontal/ Vertical Wall-Mounted
Machine Net Weight	65kg
Support Video Encoding Fromat	MPEG-1, MPEG-2, AVI (3.11), XVID, H264
Support Image Format	BMP, JPEG, PNG, GIF
Support Audio Encoding Format	MPEG-1 Layer I II 1112.0, MPEG-4 AAC LCS.1 / HE AACS.1 / BSAC2.0, WAV 24-bit Linear PCM7.1
Volume	Adjusted by remote control
Auto Power On & Off	Support
Play Mode	Loop, insertion, timing, scheduled times play mode
Memory Mode Protection	Design with safety lock
RJ-45 Interface	10m / 100m x 1
USB2.0	**x4**
Infrared Input	Support
Power Supply Spec.	Voltage Range: 1OOVac to 240Vac
Speaker Power	10W
Max Consumption	320W
Stand-by Consumption	2W
Operating Temperature	0°c - 40°c
Operating Humidity	10% - 90%, no condensation
Storage Temperature	-20°C- 60°C

MANILA OFFICE:
231 B. Padilla St., Brgy. Santa Lucia, San Juan City, Philippines 1500
Tell.: (02) 8 631-2404

DAVAO OFFICE:
A. Bldg. 333 Gen. Douglas MacArthur Highway, Talomo District Brgy. Matina Crossing,Davao City
(082) 298 9004

AVOlutionInc
www.avolutioninc.net

AVOLUTION™

DIGITAL: POWERED BY HUMANS

65 INCH INTERACTIVE TOUCH SCREEN



iMULTI-TOUCH

AVOlution Interactive Kiosk

SPECIFICATIONS

Model Size	**65 inch**
Decoders	FULL HD Decoding Board
System	Windows
CPU (Optional)	i5 10th Gen/ 8 GB DDR4
Touch Function	IR Touch/ Capacitive Touch-
Touch Point	4 Point IR Touch/ 10 Point Capacitive Touch
Max Resolution Ratio	1920 X 1080 FDH / 3840 X 2160 4K
Viewing angle	178° (H):178° 0/) (Ratio 10)
Color	16.7M Color
Brightness	350 cd/m2
Contrast Ratio	1400:1
Response Time	Sms
Visable Area	1428.6rnm(H) x 803.52mm(V)
Storage Capacity	120G SSD
Dimensions	2130mm'"936mm*80mm
Installation	Horizontal/ Vertical Wall-Mounted
Machine Net Weight	73kg
Support Video Encoding Fromat	MPEG-1, MPEG-2, AVI (3.11), XVID, H264
Support Image Format	BMP JPEG, PNG, GIF
Support Audio Encoding Format	MPEG-1 Layer I II 1112.0, MPEG-4 AAC LCS.1 / HE AACS.1 / BSAC2.0, WAV 24-bit Linear PCM7.1
Volume	Adjusted by remote control
Auto Power On & Off	Support
Play Mode	Loop, insertion, timing, scheduled times play mode
Memory Mode Protection	Design with safety lock
RJ-45 Interface	10m / 100m x 1
USB2.0	**x4**
Infrared Input	Support
Power Supply Spec.	Voltage Range: 1OOVac to 240Vac
Speaker Power	10W
Max Consumption	320W
Stand-by Consumption	2W
Operating Temperature	0°c - 40°c
Operating Humidity	10% - 90%, no condensation
Storage Temperature	-20°C- 60°C

MANILA OFFICE:
231 B. Padilla St., Brgy. Santa Lucia, San Juan City, Philippines 1500
Tell.: (02) 8 631-2404

DAVAO OFFICE:
A. Bldg. 333 Gen. Douglas MacArthur Highway, Talomo District Brgy. Matina Crossing,Davao City
(082) 298 9004

AVOlutionInc
www.avolutioninc.net